interruption of the entertainment continuity and at the conclusion thereof.

- (c) Where more than one aural broadcast STL or intercity relay station is employed in an integrated relay system, the station at the point of origination may originate the transmission of the call signs of all of the stations in the relay system.
- (d) Aural broadcast microwave booster stations will be assigned individual call signs. However, station identification will be accomplished by the retransmission of identification as provided in paragraph (a) of this section.
- (e) Voice transmissions shall normally be employed for station identification. However, other methods of station identification may be permitted or required by the Commission.

[28 FR 13716, Dec. 14, 1963, as amended at 42 FR 36830, July 18, 1977; 42 FR 38178, July 27, 1977; 45 FR 26067, Apr. 17, 1980; 49 FR 7130, Feb. 27, 1984]

Subpart F—Television Broadcast Auxiliary Stations

§ 74.600 Eligibility for license.

A license for a station in this subpart will be issued only to a television broadcast station, a television broadcast network-entity, a low power television station, or a television translator station.

[52 FR 7142, Mar. 9, 1987]

$\$\,74.601$ Classes of TV broadcast auxiliary stations.

- (a) TV pickup stations. A land mobile station used for the transmission of TV program material and related communications from scenes of events occurring at points removed from TV broadcast station studios to TV broadcast or low power TV stations or other purposes as authorized in §74.631.
- (b) TV STL station (studio-transmitter link). A fixed station used for the transmission of TV program material and related communications from the studio to the transmitter of a TV broad-

cast or low power TV station or other purposes as authorized in §74.631.

- (c) *TV relay station*. A fixed station used for transmission of TV program material and related communications for use by TV broadcast and low power TV stations or other purposes as authorized in §74.631.
- (d) TV translator relay station. A fixed station used for relaying programs and signals of TV broadcast stations to LPTV, TV translator, and to other communications facilities that the Commission may authorize or for other purposes as permitted by §74.631.
- (e) TV broadcast licensee. Licensees and permittees of both TV broadcast and low power TV stations, unless specifically otherwise indicated.
- (f) *TV microwave booster station*. A fixed station in the TV broadcast auxiliary service that receives and amplifies signals of a TV pickup, TV STL, TV relay, or TV translator relay station and retransmits them on the same frequency.

[47 FR 21496, May 18, 1982, as amended at 48 FR 17091, Aug. 21, 1983; 49 FR 7130, Feb. 27, 1984]

§74.602 Frequency assignment.

(a) The following frequencies are available for assignment to television pickup, television STL, television relay and television translator relay stations. The band segments 17,700-18,580 and 19,260-19,700 MHz are available for broadcast auxiliary stations as described in paragraph (g) of this section. Additionally, the band 38.6-40.0 GHz is available for assignment without channel bandwidth limitation to TV pickup stations on a secondary basis to fixed stations. The band segment 6425-6525 MHz is available for broadcast auxiliary stations as described in paragraph (j) of this section. Broadcast network-entities may also use the 1990-2110, 6425-6525 and 6875-7125 MHz bands for mobile television pickup only.